

View Online at <https://aerobasegroup.com/nsn/4720-00-455-0574>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.485 inches

Temperature Rating:

-67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response

Outside Diameter:

1.015 inches

Minimum Inside Bending Radius:

6.500 inches

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

14 1st end

Burst Test Pressure:

12000.0 pounds per square inch

Layer Composition And Location:

1st layer spirally laid corrosion resistant steel wire and 2nd layer spirally wrapped polytetrafluoroethylene fabric and 3rd layer spirally laid corrosion resistant steel wire and 4th layer spirally wrapped polytetrafluoroethylene fabric and 5th layer spirally laid corrosion resistant steel wire and 6th layer spirally wrapped polytetrafluoroethylene fabric and 7th layer spirally laid corrosion resistant steel wire and 8th layer spirally wrapped polytetrafluoroethylene fabric and outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

3000.0 pounds per square inch

Thread Size:

0.875 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

76.500 inches working

Media For Which Designed:

Fumigant and fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0