Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-457-5965

Cro	oss Sectional Shape:
Ro	und
Th	read Class:
2b	1st end
Th	read Direction:
Riç	ht-hand 1st end
Ins	ide Diameter:
1.3	75 inches
Te	mpurature Rating:
-40	0.0 degrees fahrenheit and 275.0 degrees fahrenheit single response
Ou	tside Diameter:
1.7	50 inches
Miı	nimum Inside Bending Radius:
11.	000 inches
Ex	terior Color:
Na	tural
Co	nnection Style:
Sw	ivel nut flare 1st end
En	d Connection Design:
Str	aight 1st end
Co	nnection Type:
Thr	readed internal tube 1st end
Th	ready Qty Per Inch (tpi):
12	1st end
Bu	rst Test Pressure:
20(	00.0 pounds per square inch
La	yer Composition And Location:
2nc	d layer rubber impregnated braided fabric and 1st layer braided steel wire and outer layer rubber impregnated braided fabric
Ма	ximum Operating Pressure:
50(	0.0 pounds per square inch
Th	read Size:
1.8	75 inches 1st end
Sea	at Angle:
37.	0 degrees 1st end
Hy	drostatic Test Pressure:
100	00.0 pounds per square inch
Ou	ter Covering Environmental Protection:
Oil	resistant
Ins	ide Surface Condition:
Sm	looth
Ме	asuring Method And Length:
20	000 inches working

Nonmetallic Hose Assembly - Page 2 of 2



Media For Which Designed:

Fuel/oil, hydrocarbon and air and water single response

**Thread Series Designator:** 

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0