## NSN 4720-00-457-6512

**Cross Sectional Shape:** 

**Thread Direction:** 

Nptf 1st end

Round

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-457-6512

Right-hand 1st end			
Inside Diameter:			
0.375 inches			
Tempurature Rating:			
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response			
Outside Diameter:			
0.750 inches			
Minimum Inside Bending Radius:			
3.000 inches			
Exterior Color:			
Red			
Connection Style:			
Plain 1st end			
End Connection Design:			
Straight 1st end			
Connection Type:			
Threaded external pipe 1st end			
Thready Qty Per Inch (tpi):			
18 1st end			
Burst Test Pressure:			
1200.0 pounds per square inch			
Layer Composition And Location:			
2nd layer braided cotton cord and 1st layer braided cotton cord and outer layer molded rubber			
Maximum Operating Pressure:			
300.0 pounds per square inch			
Thread Size:			
0.250 inches 1st end			
Hydrostatic Test Pressure:			
600.0 pounds per square inch			
Outer Covering Environmental Protection:			
Abrasion resistant and oil resistant and weatherproof			
Inside Surface Condition:			
Smooth			
Measuring Method And Length:			
14.500 inches			
Media For Which Designed:			
Air and agricultural spray solution and fuel/oil, hydrocarbon single response			
Thread Series Designator:			

## NSN 4720-00-457-6512

Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:	She	lf	Life:
-------------	-----	----	-------

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0