

View Online at <https://aerobasegroup.com/nsn/4720-00-457-6521>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.656 inches

Minimum Inside Bending Radius:

3.000 inches

Exterior Color:

Black

Connection Style:

Plain 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded external pipe 1st end

Burst Test Pressure:

1200.0 pounds per square inch

Layer Composition And Location:

2nd layer braided cotton cord and 1st layer braided cotton cord and outer layer molded rubber

Maximum Operating Pressure:

300.0 pounds per square inch

Thread Size:

0.250 inches 1st end

Hydrostatic Test Pressure:

600.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and oil resistant and weatherproof

Inside Surface Condition:

Smooth

Measuring Method And Length:

26.500 inches

Special Features:

Furnished with one coupling straight thd internal 0.250-18 nptf

Media For Which Designed:

Air and agricultural spray solution and fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0