NSN 4720-00-457-6521

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-457-6521

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.375 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.656 inches
Minimum Inside Bending Radius:
3.000 inches
Exterior Color:
Black
Connection Style:
Plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Burst Test Pressure:
1200.0 pounds per square inch
Layer Composition And Location:
2nd layer braided cotton cord and 1st layer braided cotton cord and outer layer molded rubber
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
26.500 inches

Media For Which Designed:

Special Features:

Air and agricultural spray solution and fuel/oil, hydrocarbon single response

Furnished with one coupling straight thd internal 0.250-18 nptf

Thread Series Designator:

Nptf 1st end

NSN 4720-00-457-6521

Nonmetallic Hose Assembly - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0