Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-459-0939

CI	ross Sectional Shape:
Ro	bund
Th	nread Class:
3b	o 1st end
Tŀ	nread Direction:
Ri	ght-hand 1st end
In	side Diameter:
0.2	219 inches
Te	empurature Rating:
-6	5.0 degrees fahrenheit and 158.0 degrees fahrenheit single response
0	utside Diameter:
0.0	625 inches
Mi	inimum Inside Bending Radius:
3.(000 inches
Ca	onnection Style:
Sv	wivel nut, flareless 1st end
Er	nd Connection Design:
St	raight 1st end
Co	onnection Type:
Th	nreaded internal tube 1st end
Tŀ	nready Qty Per Inch (tpi):
24	1 st end
Bı	urst Test Pressure:
16	000.0 pounds per square inch
La	ayer Composition And Location:
2n	nd layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire and outer layer molded rubber,
ch	loroprene
Ma	aximum Operating Pressure:
30	000.0 pounds per square inch
Tŀ	nread Size:
0.3	375 inches 1st end
Se	eat Angle:
12	2.0 degrees 1st end
Hy	ydrostatic Test Pressure:
80	000.0 pounds per square inch
0	uter Covering Environmental Protection:
AŁ	prasion resistant and oil resistant
In	side Surface Condition:
Sr	nooth
M	easuring Method And Length:
17	7.000 inches
Tŀ	nread Series Designator:
	njf 1st end

NSN 4720-00-459-0939

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

