

View Online at <https://aerobasegroup.com/nsn/4720-00-459-2491>

**Cross Sectional Shape:**

Round

**Inside Diameter:**

0.500 inches

**Tempurature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.875 inches

**Minimum Inside Bending Radius:**

7.000 inches

**Angle Between Rigid Elbow Fittings In Deg:**

0.0

**Quick Disconnect Size:**

0.500 inches 1st end

**Connection Style:**

Push (internal) 1st end

**End Connection Design:**

Elbow 1st end

**Connection Type:**

Internal quick disconnect 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

14000.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

2nd layer molded rubber

**Maximum Operating Pressure:**

3500.0 pounds per square inch

**Hydrostatic Test Pressure:**

7000.0 pounds per square inch

**Flow Angle:**

90.0 degrees 1st end

**Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant and weatherproof

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

600.000 inches working

**Special Features:**

Inner conveying tube material-rubber, buna-n; furnished with 2 dust caps, quick disconnect ends attached to assembly by 2 90 degrees street elbows

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0