Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-459-2776

| Cross Sectional Shape: |
|---|
| Round |
| Inside Diameter: |
| 0.375 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit single response and 180.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.560 inches |
| Angle Between Rigid Elbow Fittings In Deg: |
| 0.0 |
| Quick Disconnect Size: |
| 0.375 inches 2nd end |
| Connection Style: |
| Push (internal) 1st end |
| End Connection Design: |
| Elbow 2nd end |
| Connection Type: |
| Internal quick disconnect 1st end |
| Layer Composition And Location: |
| Outer layer braided polyamide cord |
| Maximum Operating Pressure: |
| 50.0 pounds per square inch |
| Hydrostatic Test Pressure: |
| 75.0 pounds per square inch |
| Flow Angle: |
| 90.0 degrees 2nd end |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 24.000 inches |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |
| A542a0 |
| |
| |