

View Online at <https://aerobasegroup.com/nsn/4720-00-459-6070>

**Cross Sectional Shape:**

Round

**Thread Class:**

2b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.750 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Flange Thickness:**

0.281 inches 2nd end

**Outside Diameter:**

Between 1.219 inches and 1.281 inches

**Minimum Inside Bending Radius:**

9.500 inches

**Flange Outside Diameter:**

1.500 inches 2nd end

**Connection Style:**

Swivel nut flare 1st end

**End Flange Construction:**

Solid 2nd end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

9000.0 pounds per square inch

**Layer Composition And Location:**

2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

2250.0 pounds per square inch

**Thread Size:**

1.062 inches 1st end

**Seat Angle:**

37.0 degrees 1st end

**Hydrostatic Test Pressure:**

4500.0 pounds per square inch

**Flow Angle:**

90.0 degrees 2nd end

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

32.000 inches

**Flange Style:**

Round w/ out bolt holes 2nd end

**Media For Which Designed:**

Hydraulic fluid, water base and fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Un 1st end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0