NSN 4720-00-460-1768

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-460-1768

| Cross Sectional Shape: | | |
|---|--|--|
| Round | | |
| Thread Class: | | |
| 3b 1st end | | |
| Thread Direction: | | |
| Right-hand 1st end | | |
| Inside Diameter: | | |
| 0.250 inches | | |
| Tempurature Rating: | | |
| -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response | | |
| Outside Diameter: | | |
| 0.469 inches | | |
| Minimum Inside Bending Radius: | | |
| 4.000 inches | | |
| Exterior Color: | | |
| Natural | | |
| Connection Style: | | |
| Swivel nut flare 1st end | | |
| End Connection Design: | | |
| Straight 1st end | | |
| Connection Type: | | |
| Threaded internal tube 1st end | | |
| Thready Qty Per Inch (tpi): | | |
| 20 1st end | | |
| Burst Test Pressure: | | |
| 1250.0 pounds per square inch | | |
| Layer Composition And Location: | | |
| Outer layer molded rubber and 1st layer braided cotton cord | | |
| Maximum Operating Pressure: | | |
| 200.0 pounds per square inch | | |
| Thread Size: | | |
| 0.438 inches 1st end | | |
| Seat Angle: | | |
| 37.0 degrees 1st end | | |
| Hydrostatic Test Pressure: | | |
| 400.0 pounds per square inch | | |
| Inside Surface Condition: | | |
| Smooth | | |
| Measuring Method And Length: | | |
| 6.875 inches working and 7.125 inches working | | |
| Media For Which Designed: | | |

Air single response

NSN 4720-00-460-1768

Nonmetallic Hose Assembly - Page 2 of 2



| Thread | Series | Designator: |
|--------|---------------|-------------|
|--------|---------------|-------------|

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0