## NSN 4720-00-460-2252

Metallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-460-2252

Inside Diameter: 0.750 inches  Outside Diameter: 1.210 inches  Minimum Inside Bending Radius: 8.000 inches  Minimum Inside Bending Radius: 8.000 inches  Inner Conveying Tube Style: Annular close-pitch corrugated End Connection Design: Straight 2nd end Connection Type: Unthreaded external tube 2nd end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum In Torr: 50.8 Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Sheff Life: N/a Unit of Measure: — Demilitarization: No Fiig: A54220	Cross Sectional Shape:
Inside Diameter: 0.750 inches Outside Diameter: 1.210 inches Minimum Inside Bending Radius: 8.000 inches Minimum Inside Bending Radius: 8.000 inches Inner Conveying Tube Style: Annular close-pitch corrugated End Connection Design: Straight 2nd end Connection Type: Unthreaded external tube 2nd end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum In Torr: 50.8 Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.3975 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: Na Unit of Measure: — Unit of Measure: — Demilitarization: No Filg:	
Outside Diameter: 1.210 inches Minimum Inside Bending Radius: 8.000 inches Inner Conveying Tube Style: Annular close-pitch corrugated End Connection Design: Straight 2nd end Connection Type: Unthreaded external tube 2nd end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum In Torr: 50.8 Measuring Method And Length: 27.250 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Sheft Life: N/a Unit of Measure: Unition Measure: U	
Outside Diameter:  1.210 inches Minimum Inside Bending Radius: 8.000 inches Inner Conveying Tube Style: Annular close-pitch corrugated End Connection Design: Straight 2nd end Connection Type: Unthreaded external tube 2nd end Features Provided: Identical ends Layer Composition And Location: Outset layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum In Torr: 50.8 Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Sheft Life: Nia Unit of Measure:	
1.210 inches  Minimum Inside Bending Radius: 8.000 inches  Inner Conveying Tube Style: Annular close-pitch corrugated End Connection Design: Straight 2nd end Connection Type: Unthreaded external tube 2nd end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum in Torr: 50.8 Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit of Measure:	
Minimum Inside Bending Radius:  8.000 inches  Inner Conveying Tube Style: Annular close-pitch corrugated End Connection Design: Straight 2nd end Connection Type: Unthreaded external tube 2nd end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Hydrostatic Test Pressure: 50.8  Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure:	
8.000 inches  Inner Conveying Tube Style: Annular close-pitch corrugated  End Connection Design:  Straight 2nd end  Connection Type: Unthreaded external tube 2nd end  Features Provided: Identical ends  Layer Composition And Location: Outer layer braided bronze wire  Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum In Torr: 50.8  Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: Na Unit Of Measure: - Demilitarization: No Fig:	
Inner Conveying Tube Style: Annular close-pitch corrugated End Connection Design: Straight 2nd end Connection Type: Unthreaded external tube 2nd end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum In Torr: 50.8 Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.0375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure: - Demilitarization: No Fig:	
Annular close-pitch corrugated  End Connection Design: Straight 2nd end Connection Type: Unthreaded external tube 2nd end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum In Torr: 50.8 Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
End Connection Design: Straight 2nd end Connection Type: Unthreaded external tube 2nd end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum In Torr: 50.8 Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Straight 2nd end Connection Type: Unthreaded external tube 2nd end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum in Torr: 50.8 Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Connection Type: Unthreaded external tube 2nd end Features Provided: Identical ends Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum In Torr: 50.8 Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: Na Unit Of Measure: Unit Of Measure: Demilitarization: No Filg:	
Unthreaded external tube 2nd end  Features Provided: Identical ends  Layer Composition And Location: Outer layer braided bronze wire  Maximum Operating Pressure: 150.0 pounds per square inch  Hydrostatic Test Pressure: 300.0 pounds per square inch  Vacuum In Torr: 50.8  Measuring Method And Length: 27.250 inches  Outside Diameter Tube Accommodated: 0.9375 inches 2nd end  Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape  Shelf Life: N/a  Unit Of Measure:   Demilitarization: No  Fig:	
Features Provided: Identical ends  Layer Composition And Location: Outer layer braided bronze wire  Maximum Operating Pressure: 150.0 pounds per square inch  Hydrostatic Test Pressure: 300.0 pounds per square inch  Vacuum In Torr: 50.8  Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Identical ends  Layer Composition And Location:  Outer layer braided bronze wire  Maximum Operating Pressure:  150.0 pounds per square inch  Hydrostatic Test Pressure:  300.0 pounds per square inch  Vacuum In Torr:  50.8  Measuring Method And Length:  27.250 inches  Outside Diameter Tube Accommodated:  0.9375 inches 2nd end  Special Features:  Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
Layer Composition And Location: Outer layer braided bronze wire Maximum Operating Pressure: 150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum In Torr: 50.8 Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Outer layer braided bronze wire  Maximum Operating Pressure:  150.0 pounds per square inch  Hydrostatic Test Pressure:  300.0 pounds per square inch  Vacuum In Torr:  50.8  Measuring Method And Length:  27.250 inches  Outside Diameter Tube Accommodated:  0.9375 inches 2nd end  Special Features:  Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fig:	
Maximum Operating Pressure:  150.0 pounds per square inch  Hydrostatic Test Pressure:  300.0 pounds per square inch  Vacuum In Torr:  50.8  Measuring Method And Length:  27.250 inches  Outside Diameter Tube Accommodated:  0.9375 inches 2nd end  Special Features:  Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Figs:	
150.0 pounds per square inch Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum In Torr: 50.8 Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure: Demilitarization: No Figs:	
Hydrostatic Test Pressure: 300.0 pounds per square inch Vacuum In Torr: 50.8 Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
300.0 pounds per square inch Vacuum In Torr: 50.8  Measuring Method And Length: 27.250 inches Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure: Demilitarization: No Figs:	
Vacuum In Torr:  50.8  Measuring Method And Length: 27.250 inches  Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Measuring Method And Length: 27.250 inches  Outside Diameter Tube Accommodated: 0.9375 inches 2nd end Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure: Demilitarization: No Fig:	
Measuring Method And Length:  27.250 inches  Outside Diameter Tube Accommodated:  0.9375 inches 2nd end  Special Features:  Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape  Shelf Life:  N/a  Unit Of Measure:   Demilitarization:  No  Fiig:	
27.250 inches  Outside Diameter Tube Accommodated: 0.9375 inches 2nd end  Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Outside Diameter Tube Accommodated:  0.9375 inches 2nd end  Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
0.9375 inches 2nd end  Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Special Features: Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Assembly has two legs 13.625 in. Lg joined by a 90 degrees brass elbow, corrugations are filled with rubber cement and wrapped with rubber tape  Shelf Life:  N/a Unit Of Measure: Demilitarization: No Fiig:	
rubber tape  Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig:	
N/a Unit Of Measure: Demilitarization: No Fiig:	
Unit Of Measure: Demilitarization: No Fiig:	
Demilitarization:  No Fiig:	
No Fiig:	Unit Of Measure:
No Fiig:	
Fiig:	Demilitarization:
	No
A542a0	Fiig:
	A542a0