

View Online at <https://aerobasegroup.com/nsn/4720-00-460-2436>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.375 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.688 inches

Minimum Inside Bending Radius:

3.000 inches

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external tube 1st end

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, chloroprene and 1st layer braided fiber

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

0.250 inches 2nd end

Seat Angle:

30.0 degrees 2nd end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Outer Covering Environmental Protection:

Oil resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

14.500 inches

Special Features:

Nonreusable ends

Media For Which Designed:

Grease and paint and fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0