

View Online at <https://aerobasegroup.com/nsn/4720-00-460-2445>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.375 inches

**Temperature Rating:**

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

**Outside Diameter:**

0.688 inches

**Minimum Inside Bending Radius:**

3.000 inches

**Connection Style:**

Swivel nut, inverted flare 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded external tube 1st end

**Burst Test Pressure:**

1000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer molded rubber, chloroprene and 1st layer braided fiber

**Maximum Operating Pressure:**

250.0 pounds per square inch

**Thread Size:**

0.250 inches 2nd end

**Seat Angle:**

30.0 degrees 2nd end

**Hydrostatic Test Pressure:**

500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Oil resistant and ozone resistant and solvent resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

20.500 inches

**Special Features:**

Nonreusable end fittings

**Media For Which Designed:**

Grease and paint and fuel/oil, hydrocarbon single response

**Thread Series Designator:**

Nptf 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0