NSN 4720-00-460-6775

Smooth

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-460-6775

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 275.0 degrees fahrenheit single response
Outside Diameter:
0.562 inches
Minimum Inside Bending Radius:
4.625 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
8000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant and alcohol resistant and fuel resistant and water resistant and hydraulic solution resistant
Vacuum In Torr:
50.8
Inside Surface Condition:

NSN 4720-00-460-6775

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
9.000 inches working
Special Features:
Permanently attached fittings
Thread Series Designator:
Unjf 1st end
Specification Data:
96906-ms8005 government standard
Specification Or Standard:
1 class
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A542a0