

View Online at <https://aerobasegroup.com/nsn/4720-00-461-1019>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.125 inches

Temperature Rating:

-40.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

Outside Diameter:

1.500 inches

Minimum Inside Bending Radius:

9.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Thready Qty Per Inch (tpi):

12 1st end

Burst Test Pressure:

2500.0 pounds per square inch

Layer Composition And Location:

2nd layer braided corrosion resistant steel wire and outer layer rubber impregnated braided cotton cord

Maximum Operating Pressure:

600.0 pounds per square inch

Thread Size:

1.625 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1250.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant and oil resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

40.000 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unj 1st end

Specification Data:

96906-ms28741 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiq:

A542a0