Nonmetallic Hose Assembly - Page 1 of 2



fiber and outer layer rubber impregnated braided fabric

Nonmetallic Hose Assembly - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/4720-00-461-3813
Cross Sectional Shape: Round
Thread Class:
2b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.406 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response
Outside Diameter:
0.730 inches
Minimum Inside Bending Radius:
1.750 inches
Exterior Color:
Black
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal tube 1st end
Burst Test Pressure:
4000.0 pounds per square inch
Layer Composition And Location:
2nd layer braided corrosion resistant steel wire and 1st layer braided fibe
Maximum Operating Pressure:
1000.0 pounds per square inch
Thread Size:
0.750 inches 1st end
Seat Angle:
37.0 degrees 1st end
Outer Covering Environmental Protection:
Oil resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
12.000 inches
Media For Which Designed:
Air and water single response
Thread Series Designator:
Unf 1st end

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0

