

Nonmetallic Hose Assembly - Page 1 of 2	
View Online at https://aerobasegroup.com/nsn/4720-00-461-5077	
Cross Sectional Shape:	
Round	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.625 inches	
Tempurature Rating:	
-40.0 degrees fahrenheit and 300.0 degrees fahrenheit single response	
Outside Diameter:	
1.078 inches	
Connection Style:	
Plain 2nd end	
End Connection Design:	
Straight 2nd end	
Connection Type:	
Threaded external pipe 2nd end	
Burst Test Pressure:	
6000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided steel wire and 1st layer braided cotton cord and outer layer rubber impregnated braided cotton co	ord
Maximum Operating Pressure:	
1500.0 pounds per square inch	
Thread Size:	
0.750 inches 2nd end	
Seat Angle:	
37.0 degrees 1st end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
Outer Covering Environmental Protection:	
Mildew resistant and oil resistant and grease resistant	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
11.000 inches excluding end fittings	
Special Features:	
Equipped w/swivel adapterone end	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Nptf 2nd end	

Shelf Life:

N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0