NSN 4720-00-462-7695

Nonmetallic Hose Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/4720-00-462-7695 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** Between 0.391 inches and 0.437 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** Between 0.781 inches and 0.844 inches **Minimum Inside Bending Radius:** 5.500 inches **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided wire **Maximum Operating Pressure:** 2250.0 pounds per square inch **Thread Size:** 0.750 inches 1st end Seat Angle: 45.0 degrees 1st end **Hydrostatic Test Pressure:** 4500.0 pounds per square inch **Inside Surface Condition:** Smooth **Measuring Method And Length:** 30.062 inches Media For Which Designed: Fuel/oil, hydrocarbon single response **Thread Series Designator:** Unf 1st end

Shelf Life:

N/a

NSN 4720-00-462-7695

Nonmetallic Hose Assembly - Page 2 of 2



	1	:.	~	84				
ι	JN	IT	UΤ	IVI	ea	Sι	ire:	•

--

Demilitarization:

No

Fiig:

A542a0