Cross Sectional Shape:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-463-3629

Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.313 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 250.0 degrees fah	nrenheit single response
Outside Diameter:	
0.672 inches	
Minimum Inside Bending Radius:	
4.000 inches	
Exterior Color:	
Gray or black	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Reusable end fittings	
Burst Test Pressure:	
9000.0 pounds per square inch	
Layer Composition And Location:	
2nd layer braided steel wire and 1st layer braided	ed fiber and outer layer rubber impregnated braided fabric
Maximum Operating Pressure:	
2000.0 pounds per square inch	
Thread Size:	
0.562 inches 2nd end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressure:	
4500.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	
Outer Covering Environmental Protection:	
Fuel resistant and oil resistant	
Inside Surface Condition:	
Smooth	



Measuring Method And Length: 18.000 inches working Media For Which Designed: Fuel/oil, hydrocarbon single response Thread Series Designator: Unjf 2nd end Shelf Life: N/a Unit Of Measure: --

Demilitarization:

No

Fiig:

A542a0