NSN 4720-00-465-5929



Nonmetallic Hose Assembly - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4720-00-465-5929 **Cross Sectional Shape:** Round **Thread Class:** 1a 2nd end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.812 inches **Minimum Inside Bending Radius:** 5.000 inches **Exterior Color:** Natural Angle Between Rigid Elbow Fittings In Deg: 90.0 **Connection Style:** Inverted flare 1st end **End Connection Design:** Elbow 2nd end **Connection Type:** Threaded external pipe 1st end **Burst Test Pressure:** 9000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided steel wire **Maximum Operating Pressure:** 2250.0 pounds per square inch **Thread Size:** 0.750 inches 2nd end Seat Angle: 30.0 degrees 1st end **Hydrostatic Test Pressure:**

4500.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Oil resistant and weatherproof

Inside Surface Condition:

Smooth

NSN 4720-00-465-5929

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:
35.000 inches working
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A542a0