NSN 4720-00-465-5936

Nonmetallic Hose Assembly - Page 1 of 2

Air and fuel/oil, hydrocarbon and water single response



View Online at https://aerobasegroup.com/nsn/4720-00-465-5936

| Cross Sectional Shape: |
|-----------------------------------------------------------------------------------------------------------------|
| Round |
| Thread Class: |
| 2b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.625 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.078 inches |
| Minimum Inside Bending Radius: |
| 6.500 inches |
| Connection Style: |
| Swivel nut flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded internal tube 1st end |
| Features Provided: |
| Reusable end fittings |
| Thready Qty Per Inch (tpi): |
| 12 1st end |
| Burst Test Pressure: |
| 6000.0 pounds per square inch |
| Layer Composition And Location: |
| 2nd layer braided steel wire and 1st layer braided fiber and outer layer rubber impregnated braided cotton cord |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 1.062 inches 1st end |
| Seat Angle: |
| 37.0 degrees 1st end |
| Outer Covering Environmental Protection: |
| Oil resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 34.000 inches |
| Media For Which Designed: |

NSN 4720-00-465-5936

Nonmetallic Hose Assembly - Page 2 of 2



| Thread | Series | Design | nator: |
|--------|--------|--------|--------|
| | 0000 | _00.9. | |

Un 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0