Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-465-9427

Cross Sectional Shape:
Round
Inside Diameter:
0.250 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response Outside Diameter:
0.375 inches
Minimum Inside Bending Radius:
2.000 inches
Quick Disconnect Size:
0.200 inches 2nd end
Connection Style:
Push (internal) 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Internal quick disconnect 2nd end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
100.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
50.0 pounds per square inch
Hydrostatic Test Pressure:
75.0 pounds per square inch
Flow Angle:
90.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
46.375 inches
Special Features:
W/polyurethane foam sleeve
Media For Which Designed:
Water single response
Shelf Life:
N/a

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0