

View Online at <https://aerobasegroup.com/nsn/4720-00-466-0536>

Cross Sectional Shape:

Round

Inside Diameter:

4.000 inches

Temperature Rating:

-42.0 degrees fahrenheit and 75.0 degrees fahrenheit single response

Outside Diameter:

4.625 inches

Hose Or Tubing Specification/std Data:

Mil mil-h-27516 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

First End Fitting Specification/std Data:

Mil ms27025-17 standard (includes industry or association standards, individual manufactureer standards, etc.).

Quick Disconnect Size:

4.000 inches 2nd end

Connection Style:

Cam or lever (external) 2nd end

End Connection Design:

Straight 1st end

End Fitting Component And Material:

Complete fitting aluminum alloy 2nd end

Connection Type:

Internal quick disconnect 1st end

Second End Relationship With First End:

Not identical

Burst Test Pressure:

240.0 pounds per square inch

First End Swivel Action Capability:

Not included

Layer Composition And Location:

Outer layer molded rubber, chloroprene

Hydrostatic Test Pressure:

75.0 pounds per square inch

Flow Angle:

90.0 degrees 2nd end

Outer Covering Environmental Protection:

Mildew resistant

Vacuum In Torr:

381.0

Inside Surface Condition:

Smooth

Measuring Method And Length:

36.500 inches excluding end fittings

Second End Swivel Action Capability:

Not included

Special Features:

Equipped w/fed specification wwc-440b type h hose clamps and 2ea ms27030-9 gaskets

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-h-27516 spec.