Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-468-7100

New Online at https://aciobasegroup.com/nsi//4720-00-400-7100	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.204 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit and 300.0 degrees fahrenheit single response	
Outside Diameter:	
0.461 inches	
Minimum Inside Bending Radius:	
2.000 inches	
Connection Style:	
Swivel nut, flareless 1st end	
End Connection Design:	
Straight 1st end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Nuts drilled for lockwire and reusable end fittings	
Burst Test Pressure:	
6000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire, partial c	overage
Maximum Operating Pressure:	
1000.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
12.0 degrees 1st end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
Inside Surface Condition:	
Smooth	
Measuring Method And Length:	
9.500 inches working	
Media For Which Designed:	
Fuel/oil, hydrocarbon single response	
Thread Series Designator:	
Unjf 1st end	

NSN 4720-00-468-7100

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

