Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-469-4973

View Online at https://aerobasegroup.com/nsn/4720-00-469-4973
Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.188 inches
Tempurature Rating:
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single response
Outside Diameter:
0.312 inches
Minimum Inside Bending Radius:
2.000 inches
Exterior Color:
Natural
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
12000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
1500.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
3000.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:
50.8
Inside Surface Condition:
Smooth

Nonmetallic Hose Assembly - Page 2 of 2



Measuring Method And Length:

10.000 inches working

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A542a0