Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-469-8136

,	
Cross Sectional Shape:	
Round	
Thread Class:	
3b 1st end	
Thread Direction:	
Right-hand 1st end	
Inside Diameter:	
0.188 inches	
Tempurature Rating:	
-65.0 degrees fahrenheit single response and 450.0 degrees fahrenheit single respon	ise
Outside Diameter:	
0.313 inches	
Minimum Inside Bending Radius:	
2.000 inches	
Angle Between Rigid Elbow Fittings In Deg:	
180.0	
Connection Style:	
Swivel nut flare 2nd end	
End Connection Design:	
Elbow 2nd end	
Connection Type:	
Threaded internal tube 1st end	
Features Provided:	
Electrostatic discharge capability	
Burst Test Pressure:	
12000.0 pounds per square inch	
Layer Composition And Location:	
Outer layer braided corrosion resistant steel wire	
Maximum Operating Pressure:	
1500.0 pounds per square inch	
Thread Size:	
0.438 inches 1st end	
Seat Angle:	
37.0 degrees 2nd end	
Hydrostatic Test Pressure:	
3000.0 pounds per square inch	
Flow Angle:	
90.0 degrees 2nd end	
Outer Covering Environmental Protection:	
Corrosion resistant	
Vacuum In Torr:	
E0 9	

50.8

NSN 4720-00-469-8136

Nonmetallic Hose Assembly - Page 2 of 2



Inside Surface Condition: Smooth Measuring Method And Length: 8.000 inches working **Thread Series Designator:** Unjf 1st end **Specification Data:** 76301-32-721560-124 manufacturers source control Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A542a0