Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-471-3077

View Online at https://aerobasegroup.com/nsn/4720-00-471-3077
Cross Sectional Shape:
Round
Inside Diameter:
0.500 inches
Tempurature Rating:
-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Outside Diameter:
0.875 inches
Minimum Inside Bending Radius:
7.000 inches
Quick Disconnect Size:
0.500 inches 1st end
Connection Style:
Push (internal) 1st end
End Connection Design:
Straight 1st end
Connection Type:
Internal quick disconnect 1st end
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
1st layer braided steel wire and 2nd layer molded rubber and 3rd layer braided steel wire and outer layer molded rubbe
Maximum Operating Pressure:
3500.0 pounds per square inch
Hydrostatic Test Pressure:
7000.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and oil resistant and weatherproof
Inside Surface Condition:
Smooth
Measuring Method And Length:
816.000 inches working
Special Features:
Furnished with 2 dust caps
Media For Which Designed:
Fuel/oil, hydrocarbon single response
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

## NSN 4720-00-471-3077

Nonmetallic Hose Assembly - Page 2 of 2

**Fiig:** A542a0

