NSN 4720-00-471-3148

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-471-3148

| Cross Sectional Shape: |
|--|
| Round |
| Thread Direction: |
| |
| Right-hand 1st end |
| Tempurature Rating: |
| -65.0 degrees fahrenheit and 250.0 degrees fahrenheit single response |
| Outside Diameter: |
| 0.687 inches |
| Minimum Inside Bending Radius: |
| 4.000 inches |
| Connection Style: |
| Inverted flare 1st end |
| End Connection Design: |
| Straight 1st end |
| Connection Type: |
| Threaded external pipe 1st end |
| Burst Test Pressure: |
| 20000.0 pounds per square inch |
| Layer Composition And Location: |
| 2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, chloroprene |
| Maximum Operating Pressure: |
| 5000.0 pounds per square inch |
| Thread Size: |
| 0.250 inches 1st end |
| Seat Angle: |
| 30.0 degrees 1st end |
| Hydrostatic Test Pressure: |
| 10000.0 pounds per square inch |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 12.000 inches |
| Special Features: |
| Permanently attached fittings |
| Media For Which Designed: |
| Fuel/oil, hydrocarbon single response |
| Thread Series Designator: |
| Nptf 1st end |
| Shelf Life: |
| N/a |
| Unit Of Massura: |

--

NSN 4720-00-471-3148

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0