Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-471-8262

Cross Sectional Shape:
Round
hread Direction:
Right-hand 1st end
nside Diameter:
.250 inches
empurature Rating:
40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response
Dutside Diameter:
Between 0.531 inches and 0.594 inches
/inimum Inside Bending Radius:
.000 inches
Connection Style:
Plain 1st end
Ind Connection Design:
Straight 1st end
Connection Type:
hreaded external pipe 1st end
Burst Test Pressure:
000.0 pounds per square inch
ayer Composition And Location:
nd layer braided textile yarn and 1st layer braided textile yarn and outer layer molded rubber, synthet
laximum Operating Pressure:
250.0 pounds per square inch
Thread Size:
.250 inches 1st end
lydrostatic Test Pressure:
500.0 pounds per square inch
Duter Covering Environmental Protection:
Dil resistant and ozone resistant
nside Surface Condition:
Smooth
leasuring Method And Length:
5.000 inches
ledia For Which Designed:
uel/oil, hydrocarbon single response
hread Series Designator:
lpt 1st end
Shelf Life:
l/a
Init Of Measure:

NSN 4720-00-471-8262

Nonmetallic Hose Assembly - Page 2 of 2



Demilitarization:

No

Fiig:

A542a0