

View Online at <https://aerobasegroup.com/nsn/4720-00-471-8265>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

Between 0.594 inches and 0.656 inches

Minimum Inside Bending Radius:

4.000 inches

Connection Style:

Inverted flare 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded external pipe 2nd end

Burst Test Pressure:

11000.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber and 1st layer braided steel wire

Maximum Operating Pressure:

2750.0 pounds per square inch

Thread Size:

0.375 inches 1st end

Seat Angle:

30.0 degrees 2nd end

Hydrostatic Test Pressure:

5500.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

57.000 inches

Special Features:

Permanently attached fittings

Media For Which Designed:

Fuel/oil, hydrocarbon and hydraulic fluid, water base single response

Thread Series Designator:

Nptf 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0