

View Online at <https://aerobasegroup.com/nsn/4720-00-471-8357>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.750 inches

**Tempurature Rating:**

388.0 degrees fahrenheit single response

**Outside Diameter:**

1.344 inches

**Connection Style:**

Swivel nut, inverted flare 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal pipe 1st end

**Features Provided:**

Reusable end fittings

**Burst Test Pressure:**

2000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer molded rubber, composition or outer layer molded rubber, natural or outer layer molded rubber, synthetic and 1st layer rubber impregnated braided steel wire and 2nd layer rubber impregnated braided steel wire

**Maximum Operating Pressure:**

200.0 pounds per square inch

**Thread Size:**

0.750 inches 2nd end

**Hydrostatic Test Pressure:**

1250.0 pounds per square inch

**Outer Covering Environmental Protection:**

Abrasion resistant and heat resistant and ozone resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

300.000 inches

**Special Features:**

Furnished w/female spud, 0.750-14 npt, rh thd

**Media For Which Designed:**

Steam single response

**Thread Series Designator:**

Npt 2nd end

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A542a0