

View Online at <https://aerobasegroup.com/nsn/4720-00-471-8357>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Tempurature Rating:

388.0 degrees fahrenheit single response

Outside Diameter:

1.344 inches

Connection Style:

Swivel nut, inverted flare 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal pipe 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

2000.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, composition or outer layer molded rubber, natural or outer layer molded rubber, synthetic and 1st layer rubber impregnated braided steel wire and 2nd layer rubber impregnated braided steel wire

Maximum Operating Pressure:

200.0 pounds per square inch

Thread Size:

0.750 inches 2nd end

Hydrostatic Test Pressure:

1250.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and heat resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

300.000 inches

Special Features:

Furnished w/female spud, 0.750-14 npt, rh thd

Media For Which Designed:

Steam single response

Thread Series Designator:

Npt 2nd end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0