NSN 4720-00-472-1569

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-472-1569 **Cross Sectional Shape:** Round **Thread Class:** 2a 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.844 inches **Minimum Inside Bending Radius:** 5.000 inches **Exterior Color:** Black **Connection Style:** Inverted flare 1st end **End Connection Design:** Straight 1st end **Connection Type:** Threaded external pipe 1st end **Burst Test Pressure:** 16000.0 pounds per square inch **Layer Composition And Location:** 2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber **Maximum Operating Pressure:** 4000.0 pounds per square inch **Thread Size:** 0.375 inches 1st end Seat Angle: 30.0 degrees 1st end **Hydrostatic Test Pressure:** 8000.0 pounds per square inch **Outer Covering Environmental Protection:** Mildew resistant and oil resistant and oil resistant **Inside Surface Condition:** Smooth **Measuring Method And Length:** 42.000 inches

Special Features:

Permanently attached fittings

NSN 4720-00-472-1569

Nonmetallic Hose Assembly - Page 2 of 2



	Media	For	Which	Design	ed:
--	-------	-----	-------	--------	-----

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Nptf 1st end

Specification Data:

81349-mil-h-13531 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0