

View Online at <https://aerobasegroup.com/nsn/4720-00-473-0147>

**Cross Sectional Shape:**

Round

**Thread Class:**

3b 1st end

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

1.125 inches

**Temperature Rating:**

-65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response

**Outside Diameter:**

1.359 inches

**Minimum Inside Bending Radius:**

11.000 inches

**Connection Style:**

Swivel nut, flareless 1st end

**End Connection Design:**

Straight 1st end

**Connection Type:**

Threaded internal tube 1st end

**Features Provided:**

Electrostatic discharge capability

**Thready Qty Per Inch (tpi):**

12 1st end

**Burst Test Pressure:**

4000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire

**Maximum Operating Pressure:**

1000.0 pounds per square inch

**Thread Size:**

1.625 inches 1st end

**Seat Angle:**

12.0 degrees 1st end

**Hydrostatic Test Pressure:**

2000.0 pounds per square inch

**Outer Covering Environmental Protection:**

Corrosion resistant

**Vacuum In Torr:**

508.0

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

33.000 inches working

**Thread Series Designator:**

Unj 1st end

**Specification Data:**

96906-ms8001 government standard

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiq:**

A542a0