

View Online at <https://aerobasegroup.com/nsn/4720-00-473-6196>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.250 inches

**Temperature Rating:**

-20.0 degrees fahrenheit and 156.0 degrees fahrenheit single response

**Outside Diameter:**

0.594 inches

**Minimum Inside Bending Radius:**

2.000 inches

**Exterior Color:**

Black

**Hose Or Tubing Specification/std Data:**

Zz-h-461, type 2, style a specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Connection Style:**

Plain 1st end

**End Connection Design:**

Straight 1st end

**End Fitting Component And Material:**

Complete fitting copper alloy all ends

**Connection Type:**

Threaded external pipe 1st end

**Second End Relationship With First End:**

Identical

**Burst Test Pressure:**

700.0 pounds per square inch

**First End Swivel Action Capability:**

Not included

**Layer Composition And Location:**

Outer layer molded rubber, synthetic

**Maximum Operating Pressure:**

150.0 pounds per square inch

**Thread Size:**

0.250 inches 1st end

**Seat Angle:**

30.0 degrees 1st end

**Hydrostatic Test Pressure:**

350.0 pounds per square inch

**Outer Covering Environmental Protection:**

Cold resistant and light resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

600.000 inches excluding end fittings

**Special Features:**

Inner conveying tube material-rubber, synthetic

**Media For Which Designed:**

Air single response

**Thread Series Designator:**

Npt 1st end

**Specification Data:**

Zz-h-461, type 2, style a professional/industrial association specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0