## NSN 4720-00-473-9054

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-473-9054 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.851 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 450.0 degrees fahrenheit single response **Outside Diameter:** 1.140 inches **Minimum Inside Bending Radius:** 7.300 inches **Connection Style:** Swivel nut, flareless 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end Thready Qty Per Inch (tpi): 12 2nd end **Burst Test Pressure:** 3500.0 pounds per square inch **Layer Composition And Location:** Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire **Maximum Operating Pressure:** 1250.0 pounds per square inch **Thread Size:** 1.312 inches 2nd end Seat Angle: 12.0 degrees 2nd end **Hydrostatic Test Pressure:** 2500.0 pounds per square inch Flow Angle: 90.0 degrees 1st end **Inside Surface Condition:** Smooth

**Measuring Method And Length:** 33.875 inches working

**Thread Series Designator:** 

Un 2nd end

## NSN 4720-00-473-9054

Nonmetallic Hose Assembly - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A542a0