

View Online at <https://aerobasegroup.com/nsn/4720-00-475-3435>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.500 inches

Minimum Inside Bending Radius:

3.000 inches

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Reusable end fittings

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, synthetic and 1st layer braided fabric

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

0.438 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Outer Covering Environmental Protection:

Fuel resistant and mildew resistant and oil resistant and ozone resistant

Vacuum In Torr:

50.8

Inside Surface Condition:

Smooth

Measuring Method And Length:

7.500 inches working

Media For Which Designed:

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Specification Data:

96906-ms52104 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A542a0