

View Online at <https://aerobasegroup.com/nsn/4720-00-475-4782>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.365 inches

Temperature Rating:

-160.0 degrees fahrenheit and 297.0 degrees fahrenheit single response

Outside Diameter:

0.684 inches

Minimum Inside Bending Radius:

2.500 inches

Inner Conveying Tube Style:

Annular open-pitch corrugated or helical open-pitch corrugated

Exterior Color:

Natural

End Application:

Navy air technical services, liquid oxygen converter model gcu-24a and heat exchanger

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Features Provided:

Identical ends

Burst Test Pressure:

3500.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Thread Size:

0.500 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

450.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Measuring Method And Length:

25.375 inches working

Thread Series Designator:

Unf 1st end

Specification Data:

96906-ms90457 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A542a0