NSN 4720-00-475-4806

Cross Sectional Shape:

Round

Thread Class: 3b 1st end

Thread Direction: Right-hand 1st end Inside Diameter: 0.298 inches

Tempurature Rating:

Outside Diameter:

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-475-4806

0.510 inches
Minimum Inside Bending Radius:
2.500 inches
Exterior Color:
Natural
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability and reusable end fittings
Burst Test Pressure:
14000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.562 inches 2nd end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
45.0 degrees 2nd end
Outer Covering Environmental Protection:
Ethylene glycol resistant and fuel resistant and oil resistant and solvent resistant
Inside Surface Condition:
Smooth

-67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response

NSN 4720-00-475-4806

Nonmetallic Hose Assembly - Page 2 of 2



19.000 inches working

Thread Series Designator:

Unjf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0