Nonmetallic Hose Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/4720-00-476-5445

| Cross Sectional Shape:             |  |
|------------------------------------|--|
| Round                              |  |
| Thread Class:                      |  |
| 2b 1st end                         |  |
| Thread Direction:                  |  |
| Right-hand 1st end                 |  |
| Inside Diameter:                   |  |
| 0.380 inches                       |  |
| Outside Diameter:                  |  |
| 0.560 inches                       |  |
| Minimum Inside Bending Radius:     |  |
| 1.500 inches                       |  |
| Connection Style:                  |  |
| Push (internal) 1st end            |  |
| End Connection Design:             |  |
| Straight 1st end                   |  |
| Connection Type:                   |  |
| Internal quick disconnect 1st end  |  |
| Thready Qty Per Inch (tpi):        |  |
| 18 1st end                         |  |
| Layer Composition And Location:    |  |
| Outer layer braided polyamide cord |  |
| Maximum Operating Pressure:        |  |
| 400.0 pounds per square inch       |  |
| Thread Size:                       |  |
| 0.375 inches 1st end               |  |
| Hydrostatic Test Pressure:         |  |
| 600.0 pounds per square inch       |  |
| Inside Surface Condition:          |  |
| Smooth                             |  |
| Measuring Method And Length:       |  |
| 16.000 inches                      |  |
| Thread Series Designator:          |  |
| Uns 1st end                        |  |
| Shelf Life:                        |  |
| N/a                                |  |
| Unit Of Measure:                   |  |
|                                    |  |
| Demilitarization:                  |  |
| No                                 |  |
| Fiig:                              |  |
| A542a0                             |  |