NSN 4720-00-477-5658

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-477-5658

| Cross Sectional Shape: |
|---|
| Round |
| Thread Class: |
| 3b 1st end |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.625 inches |
| Tempurature Rating: |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Outside Diameter: |
| 1.015 inches |
| Minimum Inside Bending Radius: |
| 8.000 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut flare 2nd end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal tube 1st end |
| Thready Qty Per Inch (tpi): |
| 12 2nd end |
| Burst Test Pressure: |
| 6000.0 pounds per square inch |
| Layer Composition And Location: |
| Outer layer molded rubber, synthetic and 1st layer braided steel wire |
| Maximum Operating Pressure: |
| 1500.0 pounds per square inch |
| Thread Size: |
| 1.062 inches 2nd end |
| Seat Angle: |
| 37.0 degrees 2nd end |
| Hydrostatic Test Pressure: |
| 3000.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Cold resistant and oil resistant and ozone resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 20.875 inches |

NSN 4720-00-477-5658

Nonmetallic Hose Assembly - Page 2 of 2



| Media For Which Designe | Which Designe | ed |
|-------------------------|---------------|----|
|-------------------------|---------------|----|

Fuel/oil, hydrocarbon single response

Thread Series Designator:

Unf 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0