

View Online at <https://aerobasegroup.com/nsn/4720-00-477-6586>

Cross Sectional Shape:

Round

Thread Class:

3b 1st end

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.250 inches

Temperature Rating:

-65.0 degrees fahrenheit single response and 260.0 degrees fahrenheit single response

Outside Diameter:

0.375 inches

Minimum Inside Bending Radius:

6.000 inches

End Application:

Aircraft: c-135 stratolifter, e-6 tacamo, e-3a awacs, and the f-16; joint stars target radar system

Connection Style:

Swivel nut flare 1st end

End Connection Design:

Straight 1st end

Connection Type:

Threaded internal tube 1st end

Burst Test Pressure:

2200.0 pounds per square inch

Layer Composition And Location:

Outer layer braided corrosion resistant steel wire

Maximum Operating Pressure:

500.0 pounds per square inch

Thread Size:

0.500 inches 1st end

Seat Angle:

37.0 degrees 1st end

Hydrostatic Test Pressure:

1100.0 pounds per square inch

Outer Covering Environmental Protection:

Corrosion resistant

Criticality Code Justification:

Feat

Inside Surface Condition:

Smooth

Measuring Method And Length:

36.000 inches working

Special Features:

Weapon system essential

Thread Series Designator:

Unjf 1st end

Specification Data:

81349-mil-prf-26626 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

Mil-std (military Standard):

Mil-prf-26626 spec.