## NSN 4720-00-477-7182

**Cross Sectional Shape:** 

Round

Thread Class: 3b 1st end

Thread Direction:
Right-hand 1st end
Inside Diameter:
0.212 inches

**Tempurature Rating:** 

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-477-7182

-65.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response
Outside Diameter:
0.507 inches
Minimum Inside Bending Radius:
3.000 inches
Connection Style:
Swivel nut, flareless 2nd end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Burst Test Pressure:
16000.0 pounds per square inch
Layer Composition And Location:
Outer layer spirally laid corrosion resistant steel wire
Maximum Operating Pressure:
3000.0 pounds per square inch
Thread Size:
0.438 inches 1st end
Seat Angle:
12.0 degrees 2nd end
Hydrostatic Test Pressure:
6000.0 pounds per square inch
Flow Angle:
30.0 degrees 2nd end
Outer Covering Environmental Protection:
Corrosion resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
15.625 inches working

## NSN 4720-00-477-7182

Nonmetallic Hose Assembly - Page 2 of 2



Thread Series Designator:
Unjf 1st end
Specification Data:
98897-4g94420-101a manufacturers source control
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

**Fiig:** A542a0