Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-479-0102

| Croce Sectional Shane  |
|--|
| Cross Sectional Shape:<br>Round  |
|  |
| Thread Class:  |
| 3b 1st end   |
| Thread Direction:  |
| Right-hand 1st end   |
| Inside Diameter:   |
| 0.344 inches   |
| Tempurature Rating:  |
| -65.0 degrees fahrenheit and 200.0 degrees fahrenheit single response                                    |
| Outside Diameter:  |
| 0.766 inches   |
| Minimum Inside Bending Radius:   |
| 5.000 inches   |
| Connection Style:  |
| Swivel nut, flareless 2nd end  |
| End Connection Design:   |
| Straight 2nd end   |
| Connection Type:   |
| Threaded internal tube 1st end   |
| Burst Test Pressure:   |
| 14000.0 pounds per square inch   |
| Layer Composition And Location:  |
| 2nd layer braided steel wire and 1st layer braided steel wire and outer layer molded rubber, chloroprene |
| Maximum Operating Pressure:  |
| 3000.0 pounds per square inch  |
| Thread Size:   |
| 0.750 inches 1st end   |
| Seat Angle:  |
| 12.0 degrees 2nd end   |
| Hydrostatic Test Pressure:   |
| 7000.0 pounds per square inch  |
| Outer Covering Environmental Protection:   |
| Abrasion resistant and oil resistant   |
| Inside Surface Condition:  |
| Smooth   |
| Measuring Method And Length:   |
| 10.500 inches working  |
| Thread Series Designator:  |
| Unjf 1st end Shelf Life:   |
| N/a  |
|  |

Nonmetallic Hose Assembly - Page 2 of 2



Unit Of Measure:

---

Demilitarization:

No

Fiig:

A542a0