NSN 4720-00-480-0073

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-480-0073

Cross Sectional Shape:				
Round				
Thread Class:				
3b 1st end				
Thread Direction:				
Right-hand 1st end				
Inside Diameter:				
0.234 inches				
Tempurature Rating:				
-67.0 degrees fahrenheit and 158.0 degrees fahrenheit single response				
Outside Diameter:				
Between 0.453 inches and 0.500 inches				
Minimum Inside Bending Radius:				
4.000 inches				
Connection Style:				
Swivel nut flare 1st end				
End Connection Design:				
Straight 1st end				
Connection Type:				
Threaded internal tube 1st end				
Burst Test Pressure:				
1250.0 pounds per square inch				
Layer Composition And Location:				
Outer layer molded rubber and 1st layer braided cotton cord				
Maximum Operating Pressure:				
200.0 pounds per square inch				
Thread Size:				
0.438 inches 1st end				
Seat Angle:				
37.0 degrees 1st end				
Hydrostatic Test Pressure:				
400.0 pounds per square inch				
Outer Covering Environmental Protection:				
Fuel resistant and oil resistant				
Inside Surface Condition:				
Smooth				
Measuring Method And Length:				
8.875 inches working and 9.125 inches working				
Media For Which Designed:				
Air single response				
Thread Series Designator:				

Unf 1st end

NSN 4720-00-480-0073

Nonmetallic Hose Assembly - Page 2 of 2



Spec	ific	ation	Data:
------	------	-------	-------

96906-an6270 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0