NSN 4720-00-480-2105

Nonmetallic Hose Assembly - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/4720-00-480-2105 | |
|---|--|
| Cross Sectional Shape: | |
| Round | |
| Thread Class: | |
| 3b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.212 inches | |
| Tempurature Rating: | |
| -67.0 degrees fahrenheit single response and 400.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| 0.380 inches | |
| Minimum Inside Bending Radius: | |
| 1.500 inches | |
| Exterior Color: | |
| Natural | |
| Connection Style: | |
| Swivel nut, flareless 2nd end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Features Provided: | |
| Reusable end fittings | |
| Burst Test Pressure: | |
| 12000.0 pounds per square inch | |
| Layer Composition And Location: | |
| Outer layer braided corrosion resistant steel wire | |
| Maximum Operating Pressure: | |
| 3000.0 pounds per square inch | |
| Thread Size: | |
| 0.438 inches 1st end | |
| Seat Angle: | |
| 12.0 degrees 2nd end | |
| Hydrostatic Tast Prassura | |

Hydrostatic Test Pressure:

6000.0 pounds per square inch

Flow Angle:

45.0 degrees 2nd end

Inside Surface Condition:

Smooth

Measuring Method And Length:

21.000 inches working

NSN 4720-00-480-2105

Nonmetallic Hose Assembly - Page 2 of 2



| Thread Series Designator: |
|-----------------------------------|
| Unjf 1st end |
| Specification Data: |
| 96906-ms27370 government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Demilitarization:

No

Fiig:

A542a0