NSN 4720-00-480-6222

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-480-6222

Cross Sectional Shape:
Round
Thread Class:
3b 1st end
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.375 inches
Tempurature Rating:
-100.0 degrees fahrenheit and 500.0 degrees fahrenheit single response
Outside Diameter:
1.641 inches
Minimum Inside Bending Radius:
14.000 inches
Connection Style:
Swivel nut flare 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded internal tube 1st end
Features Provided:
Electrostatic discharge capability
Thready Qty Per Inch (tpi):
12 1st end
Burst Test Pressure:
3000.0 pounds per square inch
Layer Composition And Location:
Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire
Maximum Operating Pressure:
800.0 pounds per square inch
Thread Size:
1.875 inches 1st end
Seat Angle:
37.0 degrees 1st end
Hydrostatic Test Pressure:
1600.0 pounds per square inch
Outer Covering Environmental Protection:
Corrosion resistant
Vacuum In Torr:
50.8
Inside Surface Condition:

Smooth

NSN 4720-00-480-6222

Nonmetallic Hose Assembly - Page 2 of 2



Measuring	Method A	And I	Length:
-----------	----------	-------	---------

13.000 inches working

Thread Series Designator:

Unj 1st end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0