## NSN 4720-00-480-7424

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-480-7424 **Cross Sectional Shape:** Round **Thread Class:** 2b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response **Outside Diameter:** 0.625 inches **Minimum Inside Bending Radius:** 3.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 1st end **End Connection Design:** Straight 2nd end **Connection Type:** Threaded internal tube 1st end **Burst Test Pressure:** 1600.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided textile yarn **Maximum Operating Pressure:** 400.0 pounds per square inch **Thread Size:** 0.625 inches 1st end Seat Angle: 37.0 degrees 1st end **Hydrostatic Test Pressure:** 800.0 pounds per square inch **Outer Covering Environmental Protection:** Oil resistant and ozone resistant and weatherproof **Vacuum In Torr:** 254.0 **Inside Surface Condition:** Smooth

**Measuring Method And Length:** 38.000 inches

## NSN 4720-00-480-7424

**Fiig:** A542a0

Nonmetallic Hose Assembly - Page 2 of 2



Special Features:
Reusable fittings
Media For Which Designed:
Fuel/oil, hydrocarbon and hydraulic fluid, water base single response
Thread Series Designator:
Unf 1st end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No