## NSN 4720-00-481-2305

Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-481-2305 **Cross Sectional Shape:** Round **Thread Class:** 3b 1st end **Thread Direction:** Right-hand 1st end **Inside Diameter:** 0.375 inches **Tempurature Rating:** -65.0 degrees fahrenheit and 160.0 degrees fahrenheit single response **Outside Diameter:** 0.594 inches **Minimum Inside Bending Radius:** 4.000 inches **Exterior Color:** Black **Connection Style:** Swivel nut flare 2nd end **End Connection Design:** Straight 1st end **Connection Type:** Threaded internal tube 1st end **Features Provided:** Reusable end fittings Thready Qty Per Inch (tpi): 18 1st end **Burst Test Pressure:** 1000.0 pounds per square inch **Layer Composition And Location:** Outer layer molded rubber, synthetic and 1st layer braided cotton cord **Maximum Operating Pressure:** 150.0 pounds per square inch **Thread Size:** 0.562 inches 2nd end Seat Angle:

37.0 degrees 2nd end **Hydrostatic Test Pressure:** 300.0 pounds per square inch Flow Angle: 90.0 degrees 2nd end **Outer Covering Environmental Protection:** 

Abrasion resistant and fuel resistant and oil resistant

## NSN 4720-00-481-2305

Nonmetallic Hose Assembly - Page 2 of 2



Vacuum In Torr:
254.0
Inside Surface Condition:
Smooth
<b>Measuring Method And Length:</b>
17.300 inches working
Special Features:
1.74 in. Drop dim. Of elbow
Media For Which Designed:
Air single response
Thread Series Designator:
Unf 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A542a0