Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4720-00-482-2608

| Cross Sectional Shape: | |
|---|--|
| Round | |
| Thread Class: | |
| 2b 1st end | |
| Thread Direction: | |
| Right-hand 1st end | |
| Inside Diameter: | |
| 0.312 inches | |
| Tempurature Rating: | |
| -67.0 degrees fahrenheit and 400.0 degrees fahrenheit single response | |
| Outside Diameter: | |
| 0.567 inches | |
| Minimum Inside Bending Radius: | |
| 5.000 inches | |
| Connection Style: | |
| Swivel nut, flareless 1st end | |
| End Connection Design: | |
| Straight 1st end | |
| Connection Type: | |
| Threaded internal tube 1st end | |
| Features Provided: | |
| Electrostatic discharge capability | |
| Burst Test Pressure: | |
| 14000.0 pounds per square inch | |
| Layer Composition And Location: | |
| Outer layer braided corrosion resistant steel wire and 1st layer braided corrosion resistant steel wire | |
| Maximum Operating Pressure: | |
| 3000.0 pounds per square inch | |
| Thread Size: | |
| 0.562 inches 1st end | |
| Seat Angle: | |
| 12.0 degrees 1st end | |
| Hydrostatic Test Pressure: | |
| 6000.0 pounds per square inch | |
| Flow Angle: | |
| 45.0 degrees 2nd end | |
| Inside Surface Condition: | |
| Smooth | |
| Measuring Method And Length: | |
| 12.375 inches working | |
| Thread Series Designator: | |
| Unf 1st end | |
| | |

NSN 4720-00-482-2608

Nonmetallic Hose Assembly - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0

